



Senso LOVIS 10W-30

Code: 1202

Senso LOVIS is a high performance, energy conserving engine oil. It has been designed to provide excellent fuel efficiency and exceptional engine wear protection, particularly at cold start-ups. **Senso LOVIS** has been designed for use where the engine manufacturer recommends low viscosity oil such as 10W-30 or 7.5W-30. It is recommended for use in Ford AU model, imported Ford US and European models such as Festiva, Mondeo, Taurus, Explorer and the petrol Transit van. It is also suitable for many other US models such as Chrysler and Nissan where a 7.5W-30 oil is specified.

Formerly referred to as Lo-Vis Supreme

Summary of Benefits

- Rapid oil flow at start up to minimize engine wear.
- Superior sludge and varnish control for a cleaner engine.
- Reduces emissions for a cleaner environment.
- Specifically designed for modern close fitting engines.

Specifications

- API: SM/CF
- SAE Viscosity: 10W-30
- ILSAC: GF-4
- Ford: MC2-153E

Available Size

| | 1L | 5L | 8L | 20L | 205L |
|-------------------------------|--------|--------|--------|---------|----------|
| Senso LOVIS 10W-30 | 1202-1 | 1202-5 | 1202-8 | 1202-20 | 1202-205 |

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT
INFORMATION**

Senso LOVIS 10W-30

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

| | |
|---|-------|
| Specific Density at 15°C (kg/L) | 0.871 |
| Flash Point OCO (°C) | 200 |
| Pour Point (°C) | -30 |
| Kinematic Viscosity at 40°C mm ² /s (cSt) | 80 |
| Kinematic Viscosity at 100°C mm ² /s (cSt) | 11.5 |
| Viscosity Index | 150 |
| Ash (%m) | <1.0 |
| Base Number (mg KOH/g) | 5.9 |

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.