



Senso SUPREME 15W-40

Code: 1502

Senso SUPREME is a multifunctional petrol/diesel oil representing a new generation motor oil which provides better protection from piston deposits, less oil thickening and sludge deposits, and exceptional anti-wear protection under high speed high stress motoring conditions. **Senso SUPREME** has a high viscosity index, ensuring quick circulation of oil to all moving parts during cold weather starts, providing additional wear protection during this critical time of an engines operation.

Formerly referred to as Senso 5000.

Summary of Benefits

- It incorporates the latest mineral oil technology that includes the most advanced dispersant and detergent technology available to keep the engine clean and free of sludge.
- This oil offers superior wear protection under high stress conditions.
- The multi-grade properties provide rapid circulation to help overcome wear associated with cold starts, smoother idling and greater engine efficiency.

Specifications

- API: SM/CF
- SAE Viscosity: 15W-40
- ACEA: A2/B2-02, A3/B3-98
- Mercedes Benz: 229.1
- VW: 500.00, 505.00
- Ford: M2C-153E

Available Size

	1L	5L	20L	205L	1000L
Senso SUPREME 15W-40	1502-1	1502-5	1502-20	1502-205	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT
INFORMATION**

Senso SUPREME 15W-40

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.892
Kinematic Viscosity at 40°C mm ² /s (cSt)	120
Kinematic Viscosity at 100°C mm ² /s (cSt)	15.7
Ash (%)	<1.0
Viscosity Index	135
Sulphated Ash (%m)	1.09
Phosphorus Mass (%m)	0.09
Base Number (mg KOH/g)	8.57

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.