



Ultra 4000 15W-40

Code: 2001

Ultra 4000 an oil for use in high-speed, four stroke diesel engines to meet the requirements of European, American and Japanese engine manufacturers. Designed to meet 1998 emission standards and specifically compounded for use with those diesel fuels ranging in sulphur content up to 0.5% weight.

Formerly referred to as Ultra Diesel

Summary of Benefits

- Provides maximum protection for line haul and off road vehicles operating in severe conditions
- For naturally aspirated and turbo charged diesel engines requiring the best anti-wear, dispersant and detergent technology available in a multi function lubricant package

Specifications

- API: CH-4/SJ, CG-4/CF-4/CF/CF-2
- SAE Viscosity: 15W-40
- ACEA: A3, B3, E2
- Mack: EO-M, EO-M Plus
- Daimler/Chrysler: 229.1, 228.1
- MAN: 271
- Volvo: VDS-2
- Cummins: CES 20076, 20071
- MTU: Type 2
- Caterpillar: 1K, 1N

Available Size & Product Code

	5L	20L	60L	205L	1000L
Ultra 4000 15W-40	2001-5	2001-20	-	2001-205	2001-1000

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT
INFORMATION**

Ultra 4000 15W-40

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C ASTM D4052 (kg/L)	0.883
Flash Point ASTM D92 OCO (°C)	230
Pour Point ASTM D97 (°C)	-27
Kinematic Viscosity at 40°C ASTM D445 mm ² /s (cSt)	104
Kinematic Viscosity at 100°C ASTM D445 mm ² /s (cSt)	14.5
Viscosity Index ASTM D2270	140
Sulphated Ash (%)	1.37

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.