



HPDD 40W

Code: 2200

HPDD These are high quality mono-grade diesel engine oils to meet the minimum requirements of most diesel engines.

Summary of Benefits

- Provides excellent protection against corrosion and wear throughout the recommended oil drain period.
- Anti-wear and anti-oxidants have been optimised for diesel engines to provide longer oil life.
- The detergent/dispersants control soot thickening and keep pistons clean.
- **HPDD** is primarily for Detroit Diesel two stroke engines.

Specifications

- API: CF/CF-2/SG
- SAE Viscosity: 40W
- ACEA: E1
- Mercedes Benz: MB 227.1

Available Size & Product Code

	5L	20L	60L	205L	1000L
HPDD 40W	-	2200-20	-	2200-205	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.



**PRODUCT
INFORMATION**

HPDD 40W

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.892
Flash Point OCO (°C)	225
Pour Point (°C)	-15
Kinematic Viscosity at 40°C mm ² /s (cSt)	140
Kinematic Viscosity at 100°C mm ² /s (cSt)	14.8
Sulphated Ash (%)	1.03

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.