



## **Ultra MONO** 10W, 30W, 40W, 50W

Code: 2210 - 2250

**Ultra MONO** is a high performance, mid ash, mixed fleet mono-grade automotive engines oils designed for a wide range of diesel and petrol engines operating under severe conditions. Recommended for a wide range of European, Japanese and pre-1994 American makes of diesel engines. **Ultra MONO** can be used in non-engine applications such as off-highway, agriculture and stationary plant operations. Widely used in hydraulics and transmissions, where appropriate.

*Formerly referred to as Prema Diesel.*

### **Summary of Benefits**

- Special detergent provides excellent engine cleanliness.
- Provides excellent performance in mixed fleets cutting down inventory costs.
- Prolongs engine life through special anti-wear additives.

### **Specifications**

- API: CF/SJ
- SAE Viscosity: 10W, 30W, 40W, 50W
- ACEA: E2 (SAE: 30W, 40W)
- Mercedes Benz: MB 228.0 (SAE: 30W, 40W)
- MAN: 270
- US Military: MIL-L-2104F (SAE: 30W, 40W)
- US Military: MIL-L-46152D (SAE: 10W, 30W)
- SABS: 1516/17
- Mack: EO-K/2
- Japan: Japanese CD
- Allison: -4
- Detroit Diesel: DDC Category 1 (SAE: 30W, 40W)
- MTU: Category 1 (SAE: 30W, 40W)
- ZF: TE-ML 03B (SAE: 10W)

### **Storage**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT  
INFORMATION**

**Ultra MONO 10W, 30W, 40W, 50W**

**Available Size & Product Code**

	5L	20L	60L	205L	1000L
<b>Ultra MONO 10W</b>	-	2210-20	-	2210-205	-
30W	-	2230-20	-	2230-205	-
40W	-	2240-20	-	2240-205	-
50W	-	2250-20	-	2250-205	-

**Health, Safety and Environment**

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).

**Typical Characteristics**

	10W	30W	40W	50W
Specific Density at 15°C (kg/L)		0.902	0.901	
Flash Point OCO (°C)	-33	-21	-18	
Pour Point (°C)	210	225	230	
Kinematics Viscosity at 40°C mm <sup>2</sup> /s (cSt)	41.5	102	142	
Kinematics Viscosity at 100°C mm <sup>2</sup> /s (cSt)	6.2	11.5	14.4	
Sulphated Ash (%)	1.4	1.4	1.4	
Colour	Clear	Clear	Clear	

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*