



MultiFarm 15W-40

Code: 2600

MultiFarm is formulated as a Super Tractor Oil Universal for engines, transmissions, differentials, wet brake systems, power take off and hydraulic units.

Summary of Benefits

- A multifunctional oil of the highest quality for all agricultural and off road plant where an oil of this type is called for by major manufacturers.
- This high performance oil is blended for excellent results in all tractor gear boxes, main transmissions and associated machinery, as well as superior performance in agricultural hydraulic systems.

Specifications

- API: CE, CD, CF-4/SE, SF, GL-4, GL-5 (*low speed/high torque*)
- SAE Viscosity: 15W-40
- Mercedes Benz: MB 227.1
- John Deere: JDM J27, J20A, J20C
- Ford: M2C-159B, M2C 86A, 134C
- Massey Ferguson: M1139, M1135, M1127
- Case-IH: MS 1207
- Allison: C-4
- MAN: 271
- Caterpillar: TO-2
- ZF: TE-ML 06, 07
- CCMC: D2, D4

Available Size & Product Code

	5L	20L	60L	205L	1000L
MultiFarm 15W-40	-	2600-20	-	2600-205	-



**PRODUCT
INFORMATION**

MultiFarm 15W-430

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C ASTM D4052 (kg/L)	0.884
Flash Point OCO ASTM D92 (°C)	200
Pour Point ASTM D97 (°C)	-30
Kinematics Viscosity at 40°C ASTM D445 mm ² /s (cSt)	105
Kinematics Viscosity at 100°C ASTM D445 mm ² /s (cSt)	14.8
Viscosity Index, ASTM D2270	130

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.