



Auto Trans Fluid DX3

Code: 3100

Auto Trans Fluid DX3 is a transmission fluid designed for use in automatic transmissions where Dexron® III, Dexron® II or Mercon® fluids have been specified. It is also commonly used as a power steering fluid. It is suitable for use with new technology transmission components and meets the need for improved fluid stability and reliability under increased operating temperature. **Auto Trans Fluid DX3** meets the most demanding of all ATF specifications.

Summary of Benefits

- Approved for a wide range of automatic and hydraulic transmissions.
- Cost effective option to Dexron® III products.
- May be used for service fill or top up where Dexron® II, Dexron® III and Mercon® fluids are specified.
- Provides excellent protection of mobile hydraulic pumps such as those of Denison, Sperry Vickers and Sundstrand.
- Greatly improved low temperature properties for smooth cold shifts.
- Excellent shear stability for long fluid and component life.
- Has unsurpassed retention of frictional coefficient, for consistently smooth gear changes.

Specifications

- General Motors: Dexron® III (F30556)
- Caterpillar: TO-2
- Allison: C4
- Ford: Mercon®

Available Size & Product Code

	1L	5L	20L	60L	205L
Auto Trans Fluid DX3	3100-1	3100-5	3100-20	3100-60	3100-205

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT
INFORMATION**

Auto Trans Fluid DX3

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.87
Flash Point OCO (°C)	193
Pour Point (°C)	-42
Kinematic Viscosity at 40°C mm ² /s (cSt)	44.5
Kinematic Viscosity at 100°C mm ² /s (cSt)	8
Viscosity Index	150
Colour	Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.