



# Auto Trans Fluid M

Code: 3300

**Auto Trans Fluid M** has been specially developed to meet the friction co-efficient requirements of the damper clutch system in Mitsubishi Magna automatic transmissions, and is recommended for use in the KM175 and KM177 automatic transmissions fitted to Mitsubishi Magnas from January 1988.

**Auto Trans Fluid M** can be used as top up or fill for the automatic transmissions of the following Mitsubishi models: Colt, Cordia, Gallant, Lancer, Nimbus, Pajero, Starwagon and Triton. This product must not be used in Borg Warner transmissions or power steering.

### Summary of Benefits

- Meets the demanding Mitsubishi performance requirements.
- Very good gear durability from specialized additives.
- High stable fluid ideally suited to long distance towing in hot weather.
- Smooth gear changes due to higher static and dynamic co-efficient friction.
- Low noise and no vibration from the damper clutch.

### Specifications

- Mitsubishi: Magna, ES-X64022SP3
- Hyundai: Automatic Transmissions (suitable for most)

### Available Size & Product Code

	1L	5L	20L	60L	205L
<b>Auto Trans Fluid M</b>	-	3300-5	3300-20	-	-

### Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).



**PRODUCT  
INFORMATION**

**Auto Trans Fluid M**

---

**Typical Characteristics**

Specific Density at 15°C (kg/L)	0.87
Flash Point OCO (°C)	180
Pour Point (°C)	-45
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	44
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	7.52
Viscosity Index	157
Colour	Red

---

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*