



# C4 HYDRAULIC 10W

Code: 3700

**C4 Hydraulic 10W** is high performance hydraulic oil designed to satisfy a wide range of heavy-duty hydraulic equipment requirements both on and off-highway.

### Summary of Benefits

- Excellent oxidation stability ensuring long life
- Protects against rust and corrosion
- Good anti-wear protection
- Excellent air release and anti-foam properties

### Specifications

- SAE Viscosity: 10W
- MIL-L-2104D & E
- Allison: C4
- Caterpillar: TO-2

### Available Size & Product Code

	1L	5L	20L	60L	205L
<b>C4 Hydraulic 10W</b>	-	-	3700-20	-	3700-205

### Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).



**PRODUCT  
INFORMATION**

**C4 Hydraulic 10W**

---

**Typical Characteristics**

Specific Density at 15°C (kg/L)	0.88
Flash Point OCO (°C)	226
Pour Point (°C)	-33
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	39.2
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	6.3
Viscosity Index	109

---

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*