



Hydraulic Jack Oil

46

Code: 5112

Hydraulic Jack Oil 46 is a premium quality hydraulic oil made from selected base stocks and an advanced anti-wear additive. It is recommended for use in all types of hydraulic jacks and hoists. It is also suitable for use in systems that use vane, piston or gear pumps, airline lubricators, vacuum pumps, lightly loaded gear sets and bearings (such as headstocks, windmill gears) and hydraulic hoists and jacks.

Summary of Benefits

- Formulated to combat rust, oxidation, wear and foaming
- Reduces sludge formation
- Compatible with silver components
- Provides good water separation
- Compatible with other hydraulic oils

Specifications

- ISO: 46
- Denison: HF0, HF1, HF2 Vickers I-286-S, M-2950-S
- Cincinnati Milacron: P-69 (HM)
- DIN: 51524 Part 2 (HLP Type)

Available Size & Product Code

	500mL	5L	20L	60L	205L
Hydraulic Jack Oil 46	5112-500	-	-	-	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.



**PRODUCT
INFORMATION**

Hydraulic Jack Oil 46

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.872
Flash Point OCO (°C)	185
Pour Point (°C)	-15
Kinematic Viscosity at 40°C mm ² /s (cSt)	46
Kinematic Viscosity at 100°C mm ² /s (cSt)	6.1

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.