



# ComAir RS

## 32, 46, 68

Code: 7010-7012

**ComAir RS** Screw Air Compressor oil is a premium air compressor lubricant formulated from selected highly stable base stocks with a special non-hydrolyzing anti wear additive.

### Summary of Benefits

- Longer valve life due to high resistance to deposit formation and outstanding oxidation stability.
- Low wear due to excellent rust protection and high film strength.
- Low deposit forming tendency.

### Specifications

- DIN 51506
- DIN 51352

### Available Size & Codes

	5L	20L	60L	205L	1000L
<b>ComAir RS 32</b>	-	7010-20	-	7010-205	-
46	-	7011-20	-	7011-205	-
68	-	7012-20	-	7012-205	-

### Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).



**PRODUCT  
INFORMATION**

**ComAir RS 32, 46, 68**

---

**Typical Characteristics**

	<b>32</b>	<b>46</b>	<b>68</b>
Specific Density at 15°C (kg/L)	0.87	0.87	0.87
Flash Point OCO (°C)	180	199	205
Pour Point (°C)	-18	-18	-18
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	30	44	64
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	5.3	6.7	8.5
Viscosity Index	95	95	95
C.C Residue (%)	0.01	0.01	0.01

---

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*