



# Long Life Air Compressor Oil

Code: 7018

**Long Life Air Compressor Oil** is formulated from hydro cracked base stocks with special non-hydrolyzing anti-wear additive. It is suitable for rotary screw, reciprocating and centrifugal compressors operating under severe conditions.

## Summary of Benefits

- Minimum deposit forming.
- Protects compressor components from wear.
- Low wear as a result of excellent rust protection and high film strength.
- Separates readily from water.

## Specifications

- DIN51551 Part 1

## Available Size & Codes

	500ml	5L	20L	60L	205L
<b>Long Life Air Compressor Oil</b>	7018-500	7018-5	-	-	-

## Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

## Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).



**PRODUCT  
INFORMATION**

**Long Life Air Compressor Oil**

---

**Typical Characteristics**

Specific Density at 15°C (kg/L)	0.876
Flash Point OCO (°C)	205
Pour Point (°C)	-18
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	64
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	8.5
C.C Residue	0.01

---

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*