



Procoil

12, 22, 32, 46, 68, 100, 150, 220

Code: 7047 - 7054

Procoil lubricants are a range of straight mineral oils, their prime uses being for other than lubrication. They are used in the manufacturing process where they may, or may not, form a component of the finished product and where their chemical composition may be of particular importance.

Summary of Benefits

Procoil is suitable for use as carrier oils in chemical processing, diluent of additives, dust control and as extenders in the compounding of rubber, plastics and adhesives.

Application

Procoil is a paraffinic oil range often used in the rubber, plastics and adhesives industries.

Available Size & Codes

	5L	20L	60L	205L	1000L
Procoil 12	-	7047-20	-	7047-205	-
22	-	7048-20	-	7048-205	-
32	-	7049-20	-	7049-205	-
46	-	7050-20	-	7050-205	-
68	-	7051-20	-	7051-205	-
100	-	7052-20	-	7052-205	-
150	-	7053-20	-	7053-205	-
220	-	7054-20	-	7054-205	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.



**PRODUCT
INFORMATION**

Procoil 12, 22, 32, 46, 68, 100, 150, 220

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

ISO Grade	22	32	46	68	100	150	220
Specific Density at 15°C (kg/L)	0.855	0.865	0.87	0.875	0.88	0.88	0.89
Kinematic Viscosity at 40°C mm ² /s (cSt)	21	30	45.5	66	94	140	210
Kinematic Viscosity at 100°C mm ² /s (cSt)	4.5	5.1	6.8	7.9	11.4	15.2	19.5
Viscosity Index	100	98	98	97	95	95	95
Flash Point OCO (°C)	206	210	220	225	227	235	240

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.