



CR Form

Concrete Mould Release

Code: 7063

CR Form Concrete Mould Release - concrete work is normally formed. Hence, we refer to the oil as a release agent suitable for form materials, e.g. steel, wood, plywood, hardboard etc. A release agent is applied to formwork prior to placing concrete against the form. It provides a film at the formwork/concrete interface which facilitates stripping and at the same time minimises blemishes to the concrete surface.

Application

CR Form Concrete Mould Release is an economical release agent for the manufacture of concrete slabs and pre-stressed concrete, for use on steel forms only.

Available Size & Codes

	5L	20L	60L	205L	1000L
CR Form	-	7063-20	-	7063-205	7063-1000

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.854
Flash Point OCO (°C)	70
Kinematic Viscosity at 40°C mm ² /s (cSt)	5.2
Saponification Number	9.0

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.