



Syntrans MV PURE SYNTHETIC

Code: 9340

Syntrans MV Full Synthetic is a multi vehicle fully synthetic transmission fluid formulated to meet the requirements of most modern and older automatic transmissions. This advanced formulation has passed extensive testing for European, American and Asian vehicles and offers enhanced transmission shift and anti-shudder performance with high torque capacity. Suitable for extended drain intervals up to 150,000 km's for general use and 80,000 km's for heavy-duty applications, **Syntrans MV** covers a wide range of specifications making it a true multi-functional product and suitable for 6 speed transmissions.

Summary of Benefits

- Outstanding friction and anti shudder performance
- Excellent viscosity stability in operation
- Extra shear strength
- Provides high thermal stability
- Excellent resistance to oxidation
- High fretting resistance
- Cleaner components
- Reduced Oil Inventory

Specifications

- Aisin Warner AW-1
- Allison: C4, TES 295
- Audi: G052-162, G052-990, G055-025, G055-005, G055-162, G060-162
- BMW: 7045E, LA2634, LT71141, P/N 83-22-0-142-516
- Chrysler: ATFs, Mopar AS68RC
- DEXRON® II, IID, IIE, IIIF, IIIG, IIIH, VI
- Esso: LT-71141
- Ford: FNR5, MERCON® V
- Honda: ATF-Z1, DW-1
- Hyundai/Kia: SP-II, SP-III, JWS-3314, JWS-3317, SP-IV
- Hyundai: NWS-9638
- Kia: Red-1
- Idemitsu: K17



**PRODUCT
INFORMATION**

Syntrans MV

Specifications Contd.

- JASO: 1-A
- JWS: 3309, 3314, 3317, 3324
- MAN: 339F, 339-V1, 339-V2, 339-Z1, 339-Z2
- Mazda: ATF-MIII, ATF-MV
- Mercedes Benz: 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
- Mitsubishi: SP-II, SP-III, SP-IV, ATF-J2
- Nissan: 402, Matic-D, J, K, S
- Saab: 93-165-147
- Shell: 3403, LA2634, M-1375.4, M1375.5, M1375.6
- Subaru: ATF, ATF-HP
- Suzuki: 3314, 3317
- Texaco: ETL-7045E, ETL-8072B, N402
- Toyota: T-III, T-IV, WS (WS 3324)
- Voith: 55.6335.XX (G607), 55.6336.XX (G1363)
- Volvo: Pass Car (4-6sp), 97340, 97341
- VW: G052-162, G052-990, G055-025, G055-005, G055-162, G060-162
- ZF: TE-ML 03D, 04D, 05L, 09, 11B, 14A, 16L, 17C, 14B

Available Size & Product Code

	5L	20L	60L	205L	1000L
Syntrans MV	9340-5	9340-20	-	9340-205	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT
INFORMATION**

Syntrans MV

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.8462
Flash Point OCO (°C)	224
Pour Point (°C)	-44
Kinematic Viscosity at 40°C mm ² /s (cSt)	40
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.5
Viscosity Index	190
Colour	Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.