

Syntrans J PURE SYNTHETIC

Code: 9342

Syntrans J is a fully synthetic automatic transmission fluid formulated to meet the requirements of most modern and older Asian manufacturer's automatic transmissions. **Syntrans J** meets most manufacturer requirements such as JASO 1-A plus many others. It is also suitable for use in Asia Pacific OEM automatic transmissions such as Toyota and Honda. This advanced, full synthetic formulation has improved oxidation stability and shear stability, and friction durability to enhance transmission shift performance.

Summary of Benefits

- Outstanding friction and anti shudder performance
- Excellent viscosity stability in operation
- Very low pour point
- Extra shear strength
- Excellent parts material compatibility
- Provides high thermal stability
- Excellent resistance to oxidation
- High fretting resistance
- Cleaner components
- Reduced Oil Inventory

Specifications

- Toyota: Type TII, TIII, TIV, WS
- JASO: 1-A
- Mazda: ATF D III, ATF M III
- Nissan: Matic C/D/J/K
- Mitsubishi: Diamond ATF SP II, SP III, ELC-4-SP2/M
- Hyundai: SP II, SP III
- Subaru ATF
- Daihatsu: Alumix ATF Multi
- Honda: Z1
- Isuzu: Besco ATF II, ATF III
- Suzuki: ATF Oil, ATF Oil Special
- Idemitsu: K17
- Kia: SP II, SP III
- Proton: ATF-SP



**PRODUCT
INFORMATION**

Syntrans J

Available Size & Product Code

	5L	20L	60L	205L	1000L
Syntrans J	9342-5	9342-20	-	9342-205	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.8462
Flash Point OCO (°C)	224
Pour Point (°C)	-44
Kinematic Viscosity at 40°C mm ² /s (cSt)	40
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.5
Viscosity Index	190
Colour	Red

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.