



## Syntrans CVT PURE SYNTHETIC

Code: 9360

**Syntrans CVT** fluid is a unique, long drain, Continuously Variable Transmission (CVT) fluid formulated using special synthetic base stocks developed to enhance oxidation stability and thermal resistance, improve low temperature operation, impart specified friction control, improve load-carrying ability and resist corrosion and foaming tendency. **Syntrans CVT** fluid has been designed to give outstanding performance in the Van Doorne push-belt CVT's.

Note: **Syntrans CVT** is not recommended for use in the LuK Chain Type CVT's.

### Summary of Benefits

- Maximises equipment life by maintaining wear protection and oil film thickness
- Excellent shear stability for consistent shift and protection against wear
- Less deposit formation due to its use of outstanding oxidation inhibitors

### Specifications

- Nissan: NS-1 and NS-2
- Nissan: XTronic Transmissions
- ZF
- GM: Saturn DEX-CVT
- Jatco
- EZL: 799
- Mercedes Benz: MB 236.20
- Suzuki: TC
- Volvo: 4959
- Subaru
- Ford: CVT23
- Toyota: TC

Note: **Syntrans CVT** fluid is not designed for Honda CVT's.  
Use **Syntrans CVT H** for Honda full service requirements.

### Available Size & Product Code

	5L	20L	60L	205L	1000L
<b>Syntrans CVT</b>	9360-5	9360-20	-	9360-205	-



**PRODUCT  
INFORMATION**

**Syntrans CVT**

**Storage**

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

**Health, Safety and Environment**

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: [info@royallubricants.com.au](mailto:info@royallubricants.com.au).

---

**Typical Characteristics**

Specific Density at 15°C (kg/L)	0.856
Flash Point OCO (°C)	190
Pour Point (°C)	-47
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	34
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	7.1
Brookfield Viscosity at -40°C mm <sup>2</sup> /s (cP)	14,000
Viscosity Index	178
Colour	Clear

---

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*