



**PRODUCT
INFORMATION**

Syngear LS PURE SYNTHETIC

75W-90

Code: 9410

Syngear LS is a multi-grade lubricant containing a selected blend of synthetic base and extreme pressure additives, and is designed to give maximum protection to gearboxes and differentials under the most arduous operating conditions where heat and load are major factors.

Summary of Benefits

- Reduces maintenance costs
- Maximises equipment life
- Wide temperature application
- Extends drain periods

Specifications

- API: GL-5, MT-1
- SAE Viscosity: 75W-90
- Military: MIL-L-2105D
- General Motors: HN-1561, HN-2040
- Ford: MC20119A, MC2-104
- Mack: GO-J
- Borg Warner: 5M-48
- Rockwell: 0-76E, 0-76N, (Synth.75W-90)

Available Size & Codes

	1L	5L	20L	60L	205L
Syngear LS 75W-90	-	9410-5	9410-20	-	-

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.



**PRODUCT
INFORMATION**

Syngear LS 75W-90

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.

Typical Characteristics

Specific Density at 15°C (kg/L)	0.905
Flash Point OCO (°C)	207
Pour Point (°C)	-45
Kinematic Viscosity at 40°C mm ² /s (cSt)	55
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.8
Brookfield Viscosity at -40°C mm ² /s (cP)	0
Viscosity Index	152

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.