PRODUCT INFORMATION

COPPER ANTI-SEIZE COMPOUND

(Code: 9015)

Description

COPPER ANTI SEIZE COMPOUND is a superior quality, high temperature Anti-Seize and Lubricating Compound. **COPPER ANTI SEIZE COMPOUND** provides lubrication allowing easy assembly and disassembly of metal parts. It provides maximum protection in highly corrosive environments and in the most adverse temperature conditions and protects assemblies exposed to extreme temperatures.

Summary of Benefits

- Formulated To Provide Maximum Protection Against Seizure, Heat-Freeze, Galling, Rust and Corrosion.

Operating Temperature Range

Prevents Seizure Up to 1100c.

Applications

COPPER ANTI SEIZE COMPOUND is recommended for Bushings, Chains, Engines, Gaskets, Flanges, Furnaces, Heat Exchangers, Manifolds, Nuts/Bolt, Reactors, Screws, Studs, Taps, Turbines, Valve Stems, Brake Squeal. Many other applications where a copper based Anti-Seize lubricant are required**.**

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60^{o}C.

Health, Safety and Environment

Health and safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Royal Precision Lubricants on (03) 9553-0840.

Typical Characteristics

Appearance	Flecked, gold colour
NLGI Type	1.5
Soap Type	Bentone
Penetration Worked at 25^{o}C	290 min - 320 max
Dropping Point ^{o}C	does not melt
Base Oil	Paraffinic, oxidation stable
Viscosity, cSt at 40^{o}C	500
at 100^{o}C	32
Solids content, %wt	21

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Royal Precision Lubricants
PO Box 642
Moorabbin Vic 3189
Telephone: (03) 9553 0840
Fax: (03) 9553 0843
E-mail: info@royallubricants.com.au