PRODUCT INFORMATION

Eco BR100: BRICK MOULD RELEASE

(CODE: 7061)

Description

Eco BR100 is a fully biodegradable ester-based release agent specifically designed for brick and roof tile applications.

Contains special additives to prevent clay from sticking to moulds, cutting wires and dies from extruder machines.

Application

General applications for Eco BR100: Roof Tiles
Bricks.

The product can be applied by brush, roller or a mop-like device, but an air-spray system s highly recommended. By spraying the product one achieves a fine is that evenly distributes over the moulds, preventing product concentration spots.

It is highly recommended that application method, drying time and mould surface preparation be thoroughly examined to determine the applicable production parameters. Application levels will depend on mould size, shape and material but as a basic guide: 2-5 g per square meter of mould surface should be a good starting point.

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60^{o}C.

Health, Safety and Environment

Health and safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet which can be obtained by contacting Royal Precision Lubricants on (03) 9553 0840.

Typical characteristics

Moisture	0.1%
Colour	10 Gardner (max.)
Viscosity @ 25ºC mPa.s	50-10 (max.)
Density @ 25ºC. g/cm^3	.88 (approx)
Acid Value	Less than 1
Cloud Point	-5ºC

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Royal Precision Lubricants
PO Box 642
Moorabbin Vic 3189
Telephone: (03) 9553 0840
Fax: (03) 9553 0843
E-mail: info@royallubricants.com.au