



PRODUCT INFORMATION

PREMIX 50/50 EL COOLANT

(CODE: 7094)

Description

ROYAL Extended Life Coolant Pre-Mixed 50/50 is a premium performance, environmentally sensitive pre-diluted coolant, anti-freeze and corrosion inhibitor, based on extended life organic acid plus an additional nitrite corrosion inhibitor in ethylene glycol. Provides long term protection of the cooling systems of heavy and light duty diesel engines and gasoline engines. Specifically designed for use where the engine manufacturer requires nitrite inhibited product (eg Caterpillar).

Summary of benefits

- Complete cooling system protection
- Extended service life
- Reduced maintenance costs

Specifications

- Caterpillar EC-1
- Cummins
- Detroit Diesel
- Mack trucks (014 GS 17009)
- Paccar (Kenworth and DAF Trucks)
- International
- Volvo Trucks (North America)
- Freightliner
- Thermo-King
- TMC RP329
- Meets the phosphate free requirements of European manufacturers
- Meets the silicate free requirements of Japanese manufacturers
- ASTM D6210
- ASTM D4985
- ASTM D3306

Applications

Heavy duty diesel engines fitted with "wet" or "dry" liners, in both on and off highway service.

Light duty commercial vehicle gasoline and diesel engines.

Passenger car gasoline and diesel engines.

Royal Precision Lubricants
PO Box 642
Moorabbin Vic 3189
Telephone: (03) 9553 0840
Fax: (03) 9553 0843
E-mail: info@royallubricants.com.au



PRODUCT INFORMATION

High temperature aluminium engine blocks.

Recommended maximum service intervals are:

Heavy duty diesel, on-road	1.2 Million km or 8 years
Heavy duty diesel, off-road	15,000 hours or 8 years
Passenger car & light truck commercial vehicles	250,000 km or 5 years

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health and safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Royal Precision Lubricants on (03) 9553-0840.

Royal Precision Lubricants
PO Box 642
Moorabbin Vic 3189
Telephone: (03) 9553 0840
Fax: (03) 9553 0843
E-mail: info@royallubricants.com.au