



**PRODUCT
INFORMATION**

ROAD RANGER 50

(CODE: 4010)

Description

ROAD RANGER 50 is a purpose designed lubricant for manual gearboxes meeting specifications API GL1, Ford ESW-FM2C-85A, GM HN1223 for non-EP or mild EP type lubricants.

Applications / Benefits

- ROAD RANGER is designed for the trucking industry where manual gearboxes such as Road Ranger, Eaton, Fuller, Rockwell and Spicer are commonly fitted.
- ROAD RANGER contains anti-wear, anti-foam, oxidation, corrosion and rust inhibiting additives which are harmless to copper or soft alloy bearing materials which are often used in these type of gearboxes.

Specifications

Meets the following international performance specifications:

- API GL-1
- SAE 50
- FORD ESW-FM2C-85A
- GM HN 1223 for non-EP

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health and safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Royal Precision Lubricants on (03) 9553-0840.

Typical characteristics

	Test Method	Units	SAE 50
Density @ 15°C	ASTM D4052	kg/L	0.865
Kinematic Viscosity @ 40°C	ASTM D445	cSt	186
@ 100°C	ASTM D445	cSt	16.9
Viscosity Index	ASTM D2270	-	95
Pour Point	ASTM D97	°C	-15
Flash Point (COC)	ASTM D92	°C	226

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Royal Precision Lubricants
PO Box 642
Moorabbin Vic 3189
Telephone: (03) 9553 0840
Fax: (03) 9553 0843
E-mail: info@royallubricants.com.au