



## PRODUCT INFORMATION

# RUBBER GREASE X-9

Code:9014

### Description

**Royal Lubricants Rubber Grease** is a premium grease for Industrial, Automotive and Consumer Rubber component applications containing castor oil for use when contact with natural and/or synthetic rubber is likely to occur. **Royal Lubricants Rubber Grease** can be used as a general purpose, non-harmful grease for industrial, automotive and consumer rubber parts such as hydraulic dust covers, braking system components, seals and washers. It is specially designed for use on rubber components in hydraulic systems where compatibility with the rubber seals is essential. It is also suitable for use with other rubber components such as gaiters or boots used on these systems. This grease is also recommended in other applications where the resistance to hydrocarbon solvents is required, such as automotive shock absorbers. In the assembly of platen rollers used in the printing industry this type of grease is used as a lubricant to aid the insertion of the steel mandrel into the very tight rubber outer.

**Royal Lubricants Rubber Grease** is not recommended for the lubrication and protection of brake backing plates and plunger housings.

---

### Summary of benefits:

- Excellent lubricity
- Compatible with natural and synthetic rubbers (Will not perish rubber)
- Easy to use
- Long storage life
- Protects against rust and corrosion
- Resists hydrocarbon solvents

---

### Operating Temperature Range:

Recommended operating range is -9°C to 80°C

---

### Applications:

**Royal Lubricants Rubber Grease** is recommended for use in Hydraulic Dust Covers, Braking System Components, Seals and Washers, Automotive Shock Absorbers, Hydraulic System Components, Platen Rollers. Applications where compatibility with rubber components is essential.

### Specifications:

NLGI 2

Royal Precision Lubricants  
PO Box 642  
Moorabbin Vic 3189  
Telephone: (03) 9553 0840  
Fax: (03) 9553 0843  
E-mail: [info@royallubricants.com.au](mailto:info@royallubricants.com.au)