



**PRODUCT
INFORMATION**

ULTRA 2000 15W/40 CG/SJ

(CODE: 2000)

Description

Ultra 2000 is a high performance, heavy duty, mixed fleet, shear stable, SAE 15W-40 automotive engine oil designed for a wide range of diesel and petrol engines requiring API CG-4, CF or SJ performance. Suitable for mixed fleets containing both light and heavy duty, four cycle diesel and petrol engines including a wide range of Japanese and pre 1999 US and European diesel engines, both naturally aspirated and turbocharged, in all service conditions.

Summary of benefits

- May be used in mixed fleet operations for heavy-duty petrol engines and applications such as LPG gas engines.
- Provides excellent protection against corrosion and wear throughout the recommended oil drain period.
- Excellent shear and oxidation stability ensure adequate oil life.

Specifications

Meets the following international performance specifications:

- API CG-4 / CF / CF-2, CD, SJ
- SAE Viscosity 15W/40
- MACK EO-L
- MAN 271
- Volvo VDS
- US military MIL-L2104E and MIL-L-46152E
- Allison C-4

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health and safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Royal Precision Lubricants on (03) 9553-0840.

Typical characteristics

	Test method	Units	Value
Density @ 15°C	ASTM D4052	-	0.882
Kinematic Viscosity @ 40°C	ASTM D445	-	106
@ 100°C	ASTM D445	-	14.6
Viscosity Index	ASTM D2270	-	140
Pour Point	-	°C	-28
Closed Flash Point (PM)	-	°C	230
Ash %			<1.0

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Royal Precision Lubricants
PO Box 642
Moorabbin Vic 3189
Telephone: (03) 9553 0840
Fax: (03) 9553 0843
E-mail: info@royallubricants.com.au