

BR200: Brick Mould Release

BR200 Form Brick Mould Release - Clay products are normally extruded through a die to give the required cross sectional shape. Here we refer to the oil as a die lubricant in the extrusion process. The die lubricant is fed into the laminates of the extruder mouth of the die under controlled pressure and feed rates to suit the application, e.g. bricks, roofing tiles, pipe work, etc.

Application

BR200 Form Brick Mould Release is a lubricant release agent used in the manufacture of clay bricks and tiles. Contains special additives to prevent clay from sticking to the moulds, cutting wires and dies of extruder machines.

Product Code: 7060

Product Size: 20L, 205L, 1000L

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.885
Flash Point OCO (°C)	91
Kinematic Viscosity at 40°C mm ² /s (cSt)	4.2
Saponification Number	13.0

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

BR200: Brick Mould Release

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

*The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.*