

Ultra 2000

Premium, Heavy Duty Diesel Engine Oil

Ultra 2000 is a high performance diesel engine oil to meet the requirements of naturally aspirated and turbo-charged engines. It incorporates current anti-wear and engine cleanliness technology and controls bore polishing and glazing.

Summary of Benefits

- May be used in mixed fleet operations for heavy-duty petrol engines and applications such as LPG gas engines.
- Provides excellent protection against corrosion and wear throughout the recommended oil drain period.
- Excellent shear and oxidation stability ensure adequate oil life.

Specifications:

- API: CG-4/SJ
- SAE Viscosity: 15W-40
- ACEA: A3, B3/B4
- Mack: EOL-L
- Volvo: VDS
- Man: 270/271
- MB 228.1

Product Code: 2000

Product Size: 5L, 20L, 205L



V1.1 10/2017

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Ultra 2000

Typical Characteristics:

Density at 15°C (kg/L)	0.889
Flash Point COC (°C)	>220
Pour Point (°C)	-27
Kinematic Viscosity at 40°C mm ² /s (cSt)	112
Kinematic Viscosity at 100°C mm ² /s (cSt)	14.8
Viscosity Index	137
Total Base Number (mgKOH/g)	8.5
Sulphated Ash (%m)	1.2

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.

V1.1 10/2017

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700





Product Data Sheet

V1.1 10/2017

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

