

Chain & Bar Oil

Formulated For Excellent Adhesion and Protection

Chain & Bar Oil is a specially formulated lubricant designed for lubrication of the chain bar and sprocket on all types of chainsaws and chain driven machinery. It is made from highly refined high viscosity index base oil along with a highly effective tackiness agent and anti-wear additives to protect the chain and bar and minimise throw-off.

Summary of Benefits

- Minimises chain adjustment and chain replacement
- Excellent adhesion to the chain and bar
- High level of protection ensures longer bar and chain life
- Provides good antirust and storage protection
- Excellent penetration of chain links

Product Code: 7031 – 150; 7032 - 220

Product Size: 1L, 5L, 20L, 205L, 1000L - 7031
20L, 205L, 1000L - 7032

V1.1 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Chain & Bar Oil

Typical Characteristics:

	150	220
Density at 15°C (kg/L)	0.882	0.873
Flash Point COC (°C)	>220	>220
Pour Point (°C)	-12	-10
Kinematic Viscosity at 40°C mm ² /s (cSt)	147	210
Kinematic Viscosity at 100°C mm ² /s (cSt)	14.7	20.1
Viscosity Index	99	111

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.

V1.1 10/17

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

