

SYNTEC Power Steering Fluid

Full Synthetic for Long Life, Optimum Performance



SYNTEC Power Steering Fluid is a 100% synthetic fluid suitable for use in a wide range of power steering systems. It contains a seal swell additive to reduce leaks and an anti-shudder additive not found in Automatic Transmission Fluids (ATFs). It can be used to top up most synthetic power steering fluids.

It cannot be used in Honda or Acura power steering systems or Ford AU, BA, BF, FPV or Tickford systems, or where Vegetable Oils or Brake Fluid is specified.

Summary of Benefits:

- It can be used to top up or replace mineral power steering fluids (ATF Dexron type fluids).
- Controls seal swelling and protects pump parts against wear while providing the proper friction coefficient for proper system operation.
- Contains a unique seal conditioning agent and foam inhibitor benefiting vehicles operating under the most severe conditions.
- It can be used for complete replacement where the below specifications are called for:

Specifications:

Meets or exceeds the following international performance specifications:

- | | | |
|--|--|--------------------------------------|
| ▪ Audi/VW G 002 000 | ▪ GM P/N9985010, 1052884 | ▪ Saab PN 30 32 380 |
| ▪ Audi/VW G 002 012 | ▪ GM P/N9985835, 12345866 (cold climate) | ▪ Subaru PN KOZ09A0080 |
| ▪ General Motors 9985010 | ▪ Hyundai/Kia PSF-3 | ▪ Toyota PSF Type EH (P/N 008886-01) |
| ▪ Chrysler MS-1872 | ▪ Hyundai/Kia PSF-4 | ▪ Volvo P/N1161529 |
| ▪ Chrysler MS-5931 (P/N04883077) | ▪ MB 236.3 (P/N 000 989 88 03) | |
| ▪ Chrysler MS-9602 | ▪ MB 345.0 (P/N 001 989 24 03) | |
| ▪ Chrysler MS-10838 (P/N05142893AA) | ▪ Mitsubishi PS Fluid | |
| ▪ Ford M2C 195-A | ▪ Mitsubishi Diamond SP III | |
| ▪ Ford M2C 204-A (extended temp range) | ▪ Nissan PSF-II | |
| ▪ GM P/N88901975 | ▪ Pentosin CHF 7.1, CHF 11S | |
| ▪ GM P/N89021184 | ▪ Saab PN (45) 30 09 800 | |



V3.0 06/18

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



SYNTEC Power Steering Fluid



Product Code: 3151

Product Size: 20L, 1L

Typical Characteristics:

Density at 15°C (kg/L)	0.836
Kinematic Viscosity at 40°C mm ² /s (cSt)	27.89
Kinematic Viscosity at 100°C mm ² /s (cSt)	6.67
Viscosity Index ASTM D2270	210
Pour Point (°C) ASTM D97	-45
Colour	Green

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.

V3.0 06/18

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

