

M3 Supreme

Quality Motor Oil For Superior Protection

M3 SUPREME is a high performance engine oil that meets the requirements of modern engine manufacturers.

Summary of Benefits

- Has superior sludge and varnish control for cleaner engine.
- Very good low temperature viscometrics for reduced wear at start up.
- Engine oils described as service category SJ were first introduced in 1996 for use in current and earlier passenger cars, utilities, vans, and light truck operations under manufacturers recommended oil drain intervals.
- Suitable for use in LPG and lightly loaded diesel engines both naturally aspirated and turbo-charged.

Specifications:

- API: SJ/CF
- SAE Viscosity: 20W-50
- ACEA: A2-96 Issue 2, A3-98, B2-98, B3-98, E2-96 Issue 2
- VW: 500, 501
- Ford: ESE-M2C-153E
- MIL-L-46152E, 2104E

Product Code: 1001

Product Size: 20L, 205L

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



M3 Supreme

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.896
Flash Point OCO (°C)	225
Pour Point (°C)	-21
Kinematic Viscosity at 40°C mm ² /s (cSt)	160
Kinematic Viscosity at 100°C mm ² /s (cSt)	19.0
Viscosity Index	130

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.