

Senso Gold 15W-50

High Performance Motor Oil For Extra Protection

Senso GOLD is a super high performance product blended with the finest quality mineral base oils and top quality additive materials to provide the user with the best protection for the extensive range of vehicles requiring this specification. It gives superior engine cleanliness and wear protection.

Summary of Benefits

- Formulated using low phosphorous technology for the protection of catalytic converters in cars running on unleaded fuel.
- Low volatility of this product minimises oil consumption.
- Superior polymers maintain fluidity during cold temperature start up to protect critical bearing surfaces through rapid circulation.

Specifications:

- API: SM/CF
- SAE Viscosity: 15W-50
- ACEA: A2/B2-02, A3/B3-98, B2-02
- Ford: M2C 153E
- VW: 500, 501, 505
- BMW: Special Oil
- Daimler/Chrysler: 229.1

Product Code: 1102

Product Size: 5L, 20L, 205L

Senso Gold 15W-50

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.880
Flash Point OCO (°C)	230
Pour Point (°C)	-30
Kinematic Viscosity at 40°C mm ² /s (cSt)	130
Kinematic Viscosity at 100°C mm ² /s (cSt)	18.5
Viscosity Index	150
Ash (%m)	<1.0
Colour	Clear and bright

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.