

## Product Data Sheet

### Senso Supreme 15W-40

High Performance Engine Oil for Superior Wear Protection

**Senso SUPREME** is a multifunctional petrol/diesel oil representing a new generation motor oil which provides better protection from piston deposits, less oil thickening and sludge deposits, and exceptional anti-wear protection under high speed high stress motoring conditions. **Senso SUPREME** has a high viscosity index, ensuring quick circulation of oil to all moving parts

**Senso SUPREME** has a high viscosity index, ensuring quick circulation of oil to all moving parts during cold weather starts, providing additional wear protection during this critical time of an engines operation.

### Summary of Benefits

- It incorporates the latest mineral oil technology that includes the most advanced dispersant and detergent technology available to keep the engine clean and free of sludge.
- This oil offers superior wear protection under high stress conditions.
- The multi-grade properties provide rapid circulation to help overcome wear associated with cold starts, smoother idling and greater engine efficiency.

### Specifications:

API: SM/CF

SAE Viscosity: 15W-40

■ ACEA: A2/B2-02, A3/B3-98

Mercedes Benz: 229.1

• VW: 500.00, 505.00

Ford: M2C-153E

**Product Code:** 1502

**Product Size:** 1L, 5L, 20L, 205L





40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325 Queensland

Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700





# Product Data Sheet

## Senso Supreme 15W-40

### **Typical Characteristics:**

Specific Density at 15°C (kg/L)	0.892
Kinematic Viscosity at 40°C mm2/s (cSt)	120
Kinematic Viscosity at 100°C mm2/s (cSt)	15.7
Viscosity Index	135
Sulphated Ash (%m)	1.09
Phosphorus Mass (%m)	0.09
Ash (%)	<1.0
Base Number (mg KOH/g)	8.57

<sup>\*</sup>Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.



Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

