

Senso Heavy 25W-60

Quality Motor Oil Suitable For Older Engines

Senso HEAVY is a heavy-duty passenger car lubricant recommended for protection of engines especially where low oil pressure or high consumption is involved. Also suitable for noisy or worn engines that burn oil or blow smoke, in high ambient operating temperatures and high loading associated with caravan or trailer towing.

Summary of Benefits

- Use where low oil pressure or high consumption is involved.
- Use in noisy or worn engines.
- Use in engines that burn oil or blow smoke.
- Use in high ambient operating temperatures.
- Use where high loading associated with caravan or trailer towing.
- Use in older diesel and LPG engines.

Specifications:

- API: SJ/CF
- SAE Viscosity: 25W-60

Product Code: 1601

Product Size: 5L, 20L



Senso Heavy 25W-60

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.892
Flash Point OCO (°C)	230
Pour Point (°C)	-25
Kinematic Viscosity at 40°C mm ² /s (cSt)	260
Kinematic Viscosity at 100°C mm ² /s (cSt)	25.0
Viscosity Index	140
Ash (%m)	<1.0
Colour	Clear and bright

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.