

Product Data Sheet

Four Stroke 30W

Premium, Stationary Engine Motor Oil

Four Stroke Lawn Mower and Stationary Engine Oil is a monograde SAE Viscosity 30W crankcase oil designed for small petrol and diesel engines. It controls oil consumption and deposits and protects against rust, corrosion and wear, leading to longer engine life. Recommended for four stroke petrol lawn mower engines running on leaded, unleaded or lead replacement petrol, especially Briggs and Stratton engines. ISO for small four stroke petrol and diesel stationary engines. It is not recommended for two stroke petrol or two stroke diesel engines.

Summary of Benefits

- Meet warranty service requirements for a wide range of modern diesel and petrol engines.
- Maximise engine life by controlling deposits and protecting against wear of highly loaded components under severe service conditions.
- Reduce maintenance costs by maximising oil filter life and engine overhaul periods.
- Maintain excellent control of oil consumption.
- Protect against rust and corrosion.

Specifications:

API: SJ/CF

SAE Viscosity: 30W

ACEA: E2

■ General Motors: 6094M

• Ford: M2C-121E3

US Military: MIL-L-2104F, MIL-L-45152D
Briggs & Stratton Service: SE/SF/SG SAE 30

Japan: Japanese CD





Product Data Sheet

Four Stroke 30W

Product Code: 1830

Product Size: 1L, 5L, 20L, 205L

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.894
Kinematic Viscosity at 40°C mm2/s (cSt)	102
Kinematic Viscosity at 100°C mm2/s (cSt)	11.5
Viscosity Index	100
Sulphated Ash (%m)	1.5
Base Number D2896 (MG KOH/g)	10.7
Base Number D4739 (mg KOH/G)	9.8

^{*}Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: info@royallubricants.com.au.



40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325



Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

