

Ultra 4000 15W-40

High Performance, Heavy Duty Diesel Engine Oil

Ultra 4000 an oil for use in high-speed, four stroke diesel engines to meet the requirements of European, American and Japanese engine manufacturers. Designed to meet 1998 emission standards and specifically compounded for use with those diesel fuels ranging in sulphur content up to 0.5% weight.

Summary of Benefits

- Provides maximum protection for line haul and off road vehicles operating in severe conditions
- For naturally aspirated and turbo charged diesel engines requiring the best anti-wear, dispersant and detergent technology available in a multi function lubricant package

Specifications:

- API: CH-4/SJ, CG-4/CF-4/CF/CF-2
- SAE Viscosity: 15W-40
- ACEA: E7-04, A3, B3, E2
- Mack: EO-M, EO-M Plus
- Daimler/Chrysler: 229.1, 228.1
- MAN: M3 275
- Volvo: VDS-2
- Cummins: CES 20076, 20072, 20071
- MTU: Type 2
- Caterpillar: 1K, 1N
- Ford: M2C-1 53E, E8N-M2C-1 21B
- Global: DHD-1
- JASO: DH-1
- Allison: C-4



Ultra 4000 15W-40

Product Code: 2001

Product Size: 5L, 10L, 20L, 205L, 1000L

Typical Characteristics:

Specific Density at 15°C ASTM D4052 (kg/L)	0.883
Flash Point ASTM D92 OCO (°C)	230
Pour Point ASTM D97 (°C)	-27
Kinematic Viscosity at 40°C mm ² /s (cSt)	104
Kinematic Viscosity at 100°C mm ² /s (cSt)	14.5
Viscosity Index ASTM D2270	140
Sulphated Ash (%)	1.37

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.