

# **Product Data Sheet**

### MultiFarm 15W-40

Multi-Purpose Farm Engine, Transmission and Hydraulic Oil

**MultiFarm** is formulated as a Super Tractor Oil Universal for engines, transmissions, differentials, wet brake systems, power take off and hydraulic units. **MultiFarm** is the ideal oil to rationalise farm lubricants without loss of lubricant protection and equipment performance. Transmission & Gearboxes are completely protected due to the load carrying thermal stability of **MultiFarm**.

### Summary of Benefits

- A multifunctional oil of the highest quality for all agricultural and off road plant where an oil of this type is called for by major manufacturers.
- This high performance oil is blended for excellent results in all tractor gear boxes, main transmissions and associated machinery, as well as superior performance in agricultural hydraulic systems.

### Specifications:

API: CE, CD, CF-4/SE, SF, GL-4, GL-5 (low speed/high torque)

SAE Viscosity: 15W-40

■ Mercedes Benz: MB 227.1

John Deere: JDM J27, J20A, J20C
Ford: M2C-159B, M2C 86A, 134C

Massey Ferguson: M1139, M1135, M1127

Case-IH: MS 1207

Allison: C-4

MAN: 271

Caterpillar: TO-2

ZF: TE-ML 06, 07

CCMC: D2, D4



40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325 Queensland

Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700





# Product Data Sheet

## MultiFarm 15W-40

**Product Code:** 2600

Product Size: 20L, 205L

### Typical Characteristics:

Specific Density at 15°C (kg/L)	0.884
Flash Point OCO ASTM D92 (°C)	200
Pour Point ASTM (°C)	-30
Kinematic Viscosity at 40°C ASTM D445 mm2/s (cSt)	105
Kinematic Viscosity at 100°C ASTM D445 mm2/s (cSt)	14.8
Viscosity Index, ASTM D2270	130

<sup>\*</sup>Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: <a href="mailto:info@royallubricants.com.au">info@royallubricants.com.au</a>.



40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325



Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

