



Power Steering Fluid



Full Synthetic For Long Life, Optimum Performance

Power Steering Fluid Synthetic is a 100% synthetic fluid suitable for use in a wide range of power steering systems in European, Japanese and American vehicles. It is specifically suitable for Chrysler, Ford, Honda, Mercedes Benz, Saab and Subaru vehicles.

Summary of Benefits

- Provides optimum protection in power steering systems.
- Controls seal swelling and protects pump parts against wear while providing the proper friction coefficient for proper system operation.
- Contains a unique seal conditioning agent and foam inhibitor benefiting vehicles operating under the most severe conditions.
- Offers outstanding anti-wear performance, prevention of foaming, anti-leak additives and exceptional long life properties

Specifications:

Meets or exceeds the following international performance specifications:

- General Motors 9985935
- General Motors 9985010
- Chrysler MS-1872
- Chrysler MS-5931
- Honda PN 08206-9002 PE
- MB PN 30 09 800
- Saab PN 30 09 800
- Subaru PN KOZ09A0080



Victoria

40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland

Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



www.royallubricants.com.au

...DRIVEN BY PERFECTION





Power Steering Fluid

PURE SYNTHETIC

Product Code: 3150

Product Size: 20L, 5L, 1L

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.838
Kinematic Viscosity at 40°C mm2/s (cSt)	30
Kinematic Viscosity at 100°C mm2/s (cSt)	7.2
Viscosity Index ASTM D2270	215
Pour Point (°C) ASTM D97	-45
Colour	Red

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: <u>info@royallubricants.com.au</u>.

Victoria

40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325 Queensland Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700

