

Auto Trans 95LE

For Use In Ford 4 Speed Automatic Transmissions

Auto Trans Fluid 95LE is a quality automatic transmission fluid to meet the requirements of the four speed automatic transmissions made by BTR engineering and also of the former General Motors Dexron®11 specification.

Summary of Benefits

- This product provides superior anti-wear, oxidation control and friction performance to ensure smooth gear changes over the full service period.
- The primary end use is in the Ford Falcon and Fairlane from 1989.

Specifications:

- General Motors: Dexron®11
- BTR: 85LE, 91LE & 95LE
- BTR: Specification No's, 5M-44, 5M-52
- Ford: Part No. R1-38/R1-48

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.866
Flash Point OCO (°C)	190
Pour Point (°C)	-35
Kinematic Viscosity at 40°C mm ² /s (cSt)	37
Kinematic Viscosity at 100°C mm ² /s (cSt)	7.5
Viscosity Index	185
Colour	Bright Red

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Auto Trans 95LE

Product Code: 3200

Product Size: 1L, 5L, 20L, 60L, 205L

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.