



**PRECISION LUBRICANTS**

## Product Data Sheet

### **Gear Lube TL 75W-90**

*High Quality, Easy Shift Manual Gear Oil*

**Gear Lube TL** is a high performance multi-grade manual transmission oil designed for transmissions and transaxles, which require an API GL4, SAE Viscosity 75W-90 lubricant.

#### **Summary of Benefits**

- Maximises transmission life
- Easy gear selection

#### **Specifications:**

- API: GL-4
- SAE Viscosity: 75W-90
- Ford: ESP-M2C83-C
- Borg Warner: 5M-42
- Mitsubishi: ES-X-64021

**Product Code:** 4013

**Product Size:** 1L, 2.5L, 5L, 20L, 60L 205L



Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



## Gear Lube TL 75W-90

### Typical Characteristics:

Specific Density at 15°C (kg/L)	0.88
Flash Point OCO (°C)	189
Pour Point (°C)	-33
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	71.7
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	14.0
Viscosity Index	203

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au).