

## Agritrans 10W-30

Superior Quality Universal Tractor Transmission Fluid

**Agritrans** Universal Tractor Transmission Oil, is a multi-purpose oil suited to tractors requiring a common oil for transmissions, hydraulics, differentials, final drives, wet clutches and brakes. The anti-squawk additive ensures effective operation of wet brakes. **Agritrans** has been specifically developed to meet a wide range of specifications from most modern tractor and hydraulic pump OEM's.

### Summary of Benefits

- Superior gear wear protection.
- Correct frictional characteristics ensure quiet wet brake operation.
- Proven field performance.
- Good anti-foam characteristics.
- Excellent shear stability and thermal/oxidation stability provide long fluid life.

### Specifications:

- API: GL-4
- SAE Viscosity: 10W-30
- Case-IH: MS 1206, 1207, MS-1210
- Case New Holland: MAT 3525, 3526
- Allison: C-4
- John Deere: JDM 20A/B/C/D, JDM J14B/C, JDM J21A, JDT 303, Quatrol
- Caterpillar: TO-2
- VCE WB1101
- Ford: M2C 86-B/C, M2C-134 A/B/C/D
- ZF: TE-ML 03e, TE-ML 03F, TE-ML 054, TE-ML 06K
- KUBOTA: UDT
- AGCO, Allis, Chalmers: Power Fluid 821XL
- Deutz, Allis: 272843, 257541, 246634
- Massey Ferguson: M1127, M1135, M-1141, M-1143, M-1145
- Further product specifications available upon request.



## Agritrans 10W-30

**Product Code:** 4200

**Product Size:** 5L, 20L, 205L

### Typical Characteristics:

Specific Density at 15°C (kg/L)	0.848
Flash Point OCO (°C)	190
Pour Point (°C)	-35
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	68
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	9.2
Viscosity Index	112

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au).