

## Brake & Clutch Fluid

*High Performance, Dot 4 Brake Fluid*

**Brake and Clutch Fluid** is a moisture resistant, high performance brake fluid. It is designed for the braking systems of all cars, trucks and buses and meets the latest Australian and international standards.

### Summary of Benefits

- High Boiling Point
- Moisture Resistant
- Minimises Corrosion

### Specifications:

- AS/NZ 1960:1 1995 Grade 3, Brake Fluids (non-petroleum types)
- SAE J1703 JUN 91
- FMVSS No.116 Dot 3 and 4
- Ford ESW-FM6C-2, ESZ-M6C-55A
- GMH HN 1796

**Product Code:** 6010

**Product Size:** 1L, 5L, 20L



## Brake & Clutch Fluid

### Typical Characteristics:

Density @ 15c, kg/L	1.074
Colour	Blue
Equilibrium Boiling Point	286
Viscosity cSt @ -4 (°C)	1250
Viscosity cSt @100 (°C)	2.4
Wet ERBP (°C)	190

*\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

### Storage:

*All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.*

### Health, Safety and Environment

*A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.*

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au).