

Anti-Freeze/ Boil Coolant

Premium AFAB Glycol Based Concentrate

Anti-Freeze/Boil Coolant is a mono-ethylene glycol based product containing inhibitors to protect cooling systems from corrosion and scale formation.

Summary of Benefits

- *Lowers the freezing point*
- *Raises the boiling point*
- *Provides long term protection*

Specifications:

Meets the following international performance specifications:

- AS2108-84
- General Motors GM-6043
- AS/NZS 2108.1 1997 TYPE A
- Cummins 92T8-9
- Ford ESE-M97B44-4
- Detroit 7SE298
- Ford ESE-FM97B18-C
- Nissan NES 5059 LLC
- General Motors GM-1825M

Product Code: 6030

Product Size: 20L, 205L

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Anti-Freeze/ Boil Coolant

Typical Characteristics:

Specific Gravity	1.12
Freezing Point: 50 VLV% Solution	-34
Freezing Point 30VLV% Solution	-15
Ethylene Glycol	90%
PH (50% Water)	10.3-10.7
Colour	Green

**Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.*

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

*The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.*