

CR Form: Concrete Mould Release

CR Form Concrete Mould Release - concrete work is normally formed. Hence, we refer to the oil as a release agent suitable for form materials, e.g. steel, wood, plywood, hardboard etc. A release agent is applied to formwork prior to placing concrete against the form. It provides a film at the formwork/concrete interface which facilitates stripping and at the same time minimises blemishes to the concrete surface.

Application:

CR Form Concrete Mould Release is an economical release agent for the manufacture of concrete slabs and pre-stressed concrete, for use on steel forms only

Product Code: 7063

Product Size: 20L, 205L, 1000L

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.854
Flash Point OCO (°C)	70
Saponification Number	9.0
Kinematic Viscosity at 40°C mm ² /s (cSt)	5.2

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

CR Form: Concrete Mould Release

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.