

## Syngear IGO

Heavy Duty, Full Synthetic Industrial Gear Oil



**Syngear IGO** is a full synthetic gear oil range of high quality lubricants enhanced with sulphur/phosphorus extreme pressure additive technology providing outstanding thermal stability and high load carrying capacity.

### Summary of Benefits

- Clean gear additive technology ensures low deposit formation and enhanced filter life.
- Full Extreme Pressure (EP) performance gives maximum protection of gears against wear and shock-loading.
- Good water separation and de-emulsification characteristics means reduced down time through prolonged lubricant life and increased equipment reliability.
- High protection against corrosion and wear resulting in less maintenance.

### Specifications:

- DIN 51517 (Part 3)
- AGMA 9005 - D94
- US Steel 224
- David Brown Type E
- Hansen Transmissions
- Flender
- Suitable for Müller Weingarten equipment

**Product Code:** 7629-7634

**Product Size:** 20L, 205L

Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



## Syngear IGO



### Typical Characteristics:

	<b>ISO: 150</b>	<b>220</b>	<b>320</b>	<b>460</b>	<b>680</b>	<b>1000</b>
Specific Density at 15°C (kg/L)	0.85	0.86	0.86	0.87	0.87	0.87
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	151	220	320	460	680	1008
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	17.7	23.3	40.6	54.1	75.5	71.0
Viscosity Index ASTM	176	180	181	184	192	192
Flash Point ASTM 92 (°C)	>220	>220	>220	>220	>220	>220
Pour Point ASTM 97 (°C)	-54	-45	-48	-48	-42	-40
Load Wear Index	51	51	51	51	51	51
Weld Load	200	200	200	200	200	200

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au).