



PRECISION LUBRICANTS

Product Data Sheet

Eco ARA12: Asphalt Release

High Quality, Readily Biodegradable Release Agent



ECO ARA12 Bio Asphalt Release Agent is suitable for use on all surfaces that come in contact with asphalt and other bituminous materials. It is formulated from completely natural sources making it 90-95% biodegradable over a 30 day period. These specially selected compounds make this a premium product for the protection of all plastics and metals including brass and aluminum.

Summary of Benefits

- Prevents build up on Machinery
- Reduced costs
- User friendly
- Superior outcome
- Minimizes maintenance costs
- Easy to use
- Time and cost effective
- Multiple uses
- Requires low application rates

Recommendations

This product is suitable for applications where good adherence and effective release is required. Bio Asphalt release's advanced formulation is of particular benefit when used in environmentally sensitive areas. Used neat on asphalt plant slats or when PMB's are carried. Can be diluted for C320 AC or when used on tipper trays and other ancillary equipment.

Product Code: 9089

Product Size: 20L, 205L,1000L

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Eco ARA12: Asphalt Release



Typical Characteristics:

Density at 15°C (kg/L) approx.	0.091
Viscosity at 40°C (cSt) typical	36
Viscosity at 100°C (cSt) typical	8.5
Viscosity Index	226
Flash Point (°C)	>220
Pour Point (°C)	6

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.