

Syntec Ultra 0W-30

High Performance, Full Synthetic Engine Oil



Syntec ULTRA Full Synthetic, a 100% fully synthetic motor oil that complies with modern European emission standards. As one of the top-tier Low SAPS lubricants, it is specially designed for use in high performance passenger car and light commercial petrol and diesel engines where advanced after treatment systems such as Diesel Particulate Filters (DPF) and Three Way Catalysts (TWC) are used. **Syntec ULTRA** aligns well with many OEM performance specifications and can be used in most advance European, American and Japanese model vehicles.

Summary of Benefits

- Maximum engine life
- Reduced emissions
- Maximum power and performance
- Minimum maintenance costs
- Low oil consumption

Specifications:

- API: SM/CF
- SAE Viscosity: 0W-30
- ACEA: A5/B5-08, C3
- BMW: Long Drain, Long Life 04
- Mercedes Benz: MB 229.30, 229.51
- VW: 502.00, 505.00, 505.01
- ILSAC: GF-4
- Porsche Approved

Product Code: 9180

Product Size: 1L, 5L, 20L, 205L



Syntec Ultra 0W-30



Typical Characteristics:

Specific Gravity at 15°C (kg/L)	0.855
Flash Point OCO (°C)	216
Pour Point (°C)	-39
Kinematic Viscosity at 40°C mm ² /s (cSt)	53.8
Kinematic Viscosity at 100°C mm ² /s (cSt)	10.1
TBN (mg KOH/g)	7.1
Viscosity Index	173
Sulphated Ash (%m)	0.78

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.