



**PRECISION LUBRICANTS**

## Product Data Sheet

### Ultra 7000 5W-30

Full Synthetic, High Performance Engine Oil



**Ultra 7000 Full Synthetic** is a Long Life, 100% synthetic engine oil that complies with modern European Union emission standards. As one of the top-tier Low SAPS lubricants, it is specially designed for use in high performance passenger car and light duty vehicles fitted with diesel/petrol engines where advanced after treatment systems such as Diesel Particulate Filters (DPF) and Three Way Catalysts (TWC) are used.

#### Summary of Benefits

- Maximum engine life
- Reduced emissions
- Maximum power and performance
- Minimum maintenance costs
- Low oil consumption

#### Specifications:

- API: SN/CF
- SAE Viscosity: 5W-30
- ACEA C2/C3-10 (2010)
- ACEA C2-08 (2008)
- ACEA A5/B5-04
- ACEA A3/B4-04 (2004)
- BMW: Long Drain Long Life 04
- Mercedes Benz: MB 229.1
- VW: 502.00, 505.00, 505.01
- GM DEXOS 2



Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



## Ultra 7000 5W-30



**Product Code:** 9240

**Product Size:** 1L, 5L, 10L, 20L, 205L

### Typical Characteristics:

Specific Gravity at 15°C (kg/L)	0.855
Flash Point OCO (°C)	216
Pour Point (°C)	-39
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	64.9
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	10.9
Viscosity Index	160
TBN (mg KOH/g)	7.4

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au)