



PRECISION LUBRICANTS

Product Data Sheet

Syntec Ultra V 5W-30

Full Synthetic, Long Life Passenger Car Engine Oil



PURE SYNTHETIC

Syntec ULTRA V Full Synthetic, long life petrol & diesel, energy conserving engine oil designed for the VAG group of vehicles (Volkswagen, Audi, Skoda, SEAT) for VW engines conforming to European IV emission standard which provides the highest level of protection from combustion deposits, heat induced oil oxidation and sludge deposits. Note: Touareg R5 and V10 Tdi must use VW 503.00, 506.00, 506.01 specification lubricants. **Syntec ULTRA V** is specifically for VW vehicles but is also suitable for all late model passenger cars especially those fitted with naturally aspirated and turbocharged gasoline and diesel engines in light trucks. This low viscosity performance, enhanced by low phosphorus and sulphur formulation (Low SAPS) reduces ash formation and delivers a significant increase in DPF service life.

Summary of Benefits

- Maximum engine life
- Reduced emissions
- Maximum power and performance
- Minimum maintenance costs
- Low oil consumption

Specifications:

- SAE Viscosity: 5W-30
- ACEA: A3/B4-04 (2004)
- Mercedes Benz: MB 229.51
- VW: 504.00 (Petrol), 507.00 (Diesel)
- ILSAC: GF-4
- BMW: Long Life 04

Product Code: 9280

Product Size: 5L, 20L, 205L



Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Syntec Ultra V 5W-30



Typical Characteristics:

Specific Density at 15°C (kg/L)	0.848
Flash Point OCO (°C)	224
Pour Point (°C)	-36
Kinematic Viscosity at 40°C mm ² /s (cSt)	73
Kinematic Viscosity at 100°C mm ² /s (cSt)	12.0
Viscosity Index	167
Sulphated Ash (%m)	0.6
Phosphorus Mass (%m)	0.057
Calcium (%m)	0.139
Nitrogen (%m)	0.10
Base Number (mg KOH/g)	5.9

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au