

Product Data Sheet

Syntrans DX6

Fully Synthetic Automatic Transmission Fluid

PURE SYNTHETIC

Syntrans DX6 is a high performance, fully synthetic automatic transmission fluid that is especially developed for the requirements of General Motors **Syntrans DX6** and other manufacturer's requiring a low viscosity fluid. Syntrans DX6 also provides improved performance in older General Motor vehicles and provides better protection against rust and corrosion while the excellent foam control leads to long lasting, smooth shifting behaviour.

Summary of Benefits

- Improved anti-wear protection which contributes to extended transmission life
- Excellent anti-shudder durability
- Excellent viscosity stability in operation
- Provides high thermal stability
- Excellent resistance to oxidation

Specifications:

- Dexron VI
- JASO 1-A
- Honda DW-1
- Hyundai NWS-9638
- Mitsubishi SP-IV
- Nissan Matic-S
- Toyota WS

- Mercon LV
- Aisin Warner AW-1
- Hyundai/Kia SP-IV
- JWS 3324
- Mitsubishi ATF J2
- Saab 93 165 147
- **Product Code:** 9311

Product Size: 1L, 5L, 20L, 60L, 205L, 1000L



Victoria

40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Oueensland

Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia, 4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



www.royallubricants.com.au

...DRIVEN BY PERFECTION







Product Data Sheet

Typical Characteristics:

Specific Density at 15°C (kg/L)	0.85
Flash Point OCO (°C)	>190
Pour Point (°C)	-30
Kinematic Viscosity at 40°C mm2/s (cSt)	30
Kinematic Viscosity at 100°C mm2/s (cSt)	5.85
Viscosity Index	145
Colour	Red

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email: <u>info@royallubricants.com.au</u>.

Victoria

40 Kimberly Road, Dandenong South, Victoria Australia 3175 PO Box 4580, Dandenong South, Victoria Australia 3164 Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325 Queensland

Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504 PO Box 139, Deception Bay, Queensland, Australia, 4508 Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



www.royallubricants.com.au

...DRIVEN BY PERFECTION