

Syntrans MV

Full Synthetic, Multi-Vehicle Automatic Transmission Fluid  PURE SYNTHETIC

Syntrans MV Full Synthetic is a multi-vehicle fully synthetic transmission fluid formulated to meet the requirements of most modern and older automatic transmissions. This advanced formulation has passed extensive testing for European, American and Asian vehicles and offers enhanced transmission shift and anti-shudder performance with high torque capacity.

Suitable for extended drain intervals up to 150,000 km's for general use and 80,000 km's for heavy-duty applications, **Syntrans MV** covers a wide range of specifications making it a true multi-functional product and suitable for 6 speed transmissions.

Summary of Benefits

- Outstanding friction and anti-shudder performance
- Excellent viscosity stability in operation
- Extra shear strength
- Provides high thermal stability
- Excellent resistance to oxidation
- High fretting resistance
- Cleaner components
- Reduced Oil Inventory

Product Code: 9340

Product Size: 1L, 5L, 20L, 205L



Syntrans MV



Typical Characteristics:

Specific Density at 15°C (kg/L)	0.8462
Flash Point OCO (°C)	224
Pour Point (°C)	-44
Kinematic Viscosity at 40°C mm ² /s (cSt)	40
Kinematic Viscosity at 100°C mm ² /s (cSt)	8.5
Viscosity Index	190
Colour	Red

*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

Specifications:

- AE (LT71141 – ZF 5 Speed)
- Alfa Romeo (all vehicles)
- Aisin Warner AW-1, JWS 3309, JWS 3324, M315 A-1, T IV
- Allison C-3, C-4
- Allison TES 295
- Allison TES 389
- American Motors ATF +3 (SM7176-E, ATF+4 (MS9602)
- AS 68 RC (T IV)
- ATF Type A Suffix A
- Audi/VW G 052 025-A2
- Audi/VW G-052-162-A1
- Audi 5 HP LT 71141 (ZF 5 HP 18 FL, 19FL, 24A)
- Audi 5 HP LT 71141 (G-052-162-A1, A2)
- Audi 5 HP (ZF 5 HP 30)
- Audi G-055-025-A2 (JWS 3309)
- BMW ETL-7045, 7045E (83 22 0 026 922)
- BMW 7045E (3 series)
- BMW LA2634 BMW 5 HP LT 71141 (ZF 5 HP 18 FL, 19FL, 24A)
- BMW 5 HP LT 71141 (83 22 9 407 807)
- BMW 5 HP (ZF 5 HP 30)
- BMW ETL-8072B (83 22 0 024 359)
- BMW MINI 83 22 0 402 413 9 (JWS 3309)
- BMW 5 Series (Texaco ETL-8072B)
- Caterpillar Power Shift TO-2
- Chrysler ATF +3 (MS 7176-E)/+4 (MS 9602)
- Chrysler Dodge MOPAR AS 68 RC (T IV)
- Daimler NAG-1
- Daewoo LT 71141
- Esso LT 71141
- Fiat (All vehicles), TYPE T IV
- Ford MERCON® (XT-2-QDR, XT-2-QSM SYN)
- Ford MERCON® V
- Ford MERCON® LV
- Ford MERCON® SP
- Ford WSS M2C 922 A1, 924-A (XT-8-QAW) (JWS 3309)



PRECISION LUBRICANTS

Product Data Sheet

Syntrans MV



Specifications contd.

- GM DEXRON® II, IID, IIE, III, IIIG, IIIH
 - GM DEXRON® VI
 - GM T IV
 - GM Type A
 - Honda/Acura ATF Z1, DW-1, Premium
 - Honda Z-1
 - Hyundai NWS-9638, SP-II, SP-III, SP-IV
 - Isuzu Besco ATF II, ATF III
 - Jaguar ATF 3403 M115, LT 71141, jlm 20238
 - JASO 1-A
 - JASO 2A-02
 - JATCO FWD in Nissan, Rover 800, VW Polo (Texaco N402)
 - JATCO – Jaguar X Type 2001-2005 (Idemitsu K-17)
 - JATCO 3100 PL085
 - JEEP ATF+3, ATF+4
 - JWS 3309 (Aisin Warner)
 - JWS 3309 (T-IV)
 - JWS 3324 (WS) Kia ATF Red 1, SP-II, SP-III, SP-IV
 - MAN 339F, V1, V2, Z1, Z2, Z3
 - Mazda ATF-M III
 - Mazda ATF – MV
 - Mercedes Benz 223.1, 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.12, 236.41
 - MB ZF 4 HP20
 - MB 5 Speed 1996-2006 (Shell 3403)
 - Mini Cooper 83 22 0 402 413 9 (JWS 3309, T IV)
 - Mitsubishi Diamond SP-II, SP-III, SP-IV, Dia
 - Nissan/Infinity Matic D/J/K/S
 - NAG 1 (Jeep Cherokee), NAG 2 (Chrysler)
 - Opel (All vehicles)
 - Peugeot ZF 4 HP20
 - Porsche ATF 3403-M115, LT 71141, T IV (JWS 3309)
 - Queen J2
 - SAAB T IV (JWS 3309)
 - Saturn T IV (JWS 3309)
 - Scion (all vehicles)
 - Shell M 115
 - SP-II
 - SP-III
 - Subaru ATF, ATF HP
 - Suzuki ATF 3309
 - Texaco ETL-7045E
 - Volvo 97340, 97341, T IV (JWS 3309)
 - VW 5 HP LT 71141 (ZF 5 HP 18FL, 19FL, 24A)
 - VW 5 HP LT 71141 (VW G-052-162-A1, A2)
 - VW G-052-182-A2
 - VW 5 HP (ZF 5 HP 30)
 - Texaco ETL-8072B
 - Toyota T-II/T-IV
 - Toyota WS
 - Voith G607 G13636 (55.6336.XX)
 - Voith Turbo H55.6335.3X
 - VW TL 521 62
 - VW TL52162
 - ZF 3 and 4 speed transmissions
 - ZF TE ML 02F, 03D, 04D, 05L, 14A, 14B, 14C, 16L, 17C
 - ZF TE-ML-09
 - ZF TE-ML 11A and 11B
- NOT RECOMMENDED FOR USE**
- Ford Type F / G
 - DCTs and CVTs

Victoria
40 Kimberly Road, Dandenong South, Victoria Australia 3175
PO Box 4580, Dandenong South, Victoria Australia 3164
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504
PO Box 139, Deception Bay, Queensland, Australia, 4508
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



Syntrans MV



Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:
info@royallubricants.com.au.