

## Syntrans E



*Full Synthetic, Automatic Transmission Fluid for European Vehicles*

**Syntrans E** Full Synthetic automatic transmission fluid is blended to meet the requirements of most modern and older European automatic transmissions such as those specified by Mercedes Benz, BMW and ZF including the ZF 6 speed installed in Ford vehicles. It is a very versatile fluid and can be used in all vehicles fitted with European transmissions as a service fill including wherever ESSO ATF LT 71141 is recommended. This advanced formulation has improved oxidation stability and shear stability, and friction durability to enhance transmission shift performance.

### Summary of Benefits

- Outstanding friction and anti-shudder performance
- Excellent viscosity stability in operation
- Very low pour point
- Extra shear strength
- Excellent parts material compatibility
- Provides high thermal stability
- Excellent resistance to oxidation
- High fretting resistance
- Cleaner components
- Reduced Oil Inventory

**Product Code:** 9341

**Product Size:** 5L, 20L, 205L

Victoria  
40 Kimberly Road, Dandenong South, Victoria Australia 3175  
PO Box 4580, Dandenong South, Victoria Australia 3164  
Telephone: 61 +3 9768 2441 Fax: 61+3 9768 3325

Queensland  
Cnr Boundary Road & Potassium Street, Narangba, Queensland Australia,4504  
PO Box 139, Deception Bay, Queensland, Australia, 4508  
Telephone: 61 +7 3203 0089 Fax: 61 +7 3203 3700



## Syntrans E



### Specifications:

- Daimler Benz: DB 236.6
- ZF: TE-ML 06D/04D/09/14A/14B/14C/16L/17C
- Volvo: 97340
- Mercedes Benz: MB 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11
- Esso: LT71141
- BMW: 7045E, LA2634, LT71141
- VW/Audi: G 052-025-A2, G 052-162-A1
- Voith Diwa: 502-2, 502-3, D851, G607

### Typical Characteristics:

Specific Density at 15°C (kg/L)	0.8462
Flash Point OCO (°C)	224
Pour Point (°C)	-44
Kinematic Viscosity at 40°C mm <sup>2</sup> /s (cSt)	40
Kinematic Viscosity at 100°C mm <sup>2</sup> /s (cSt)	8.5
Viscosity Index	190
Colour	Red

\*Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute a legal liability.

## Syntrans E



### Storage:

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

### Health, Safety and Environment

A Material Safety Data Sheet (MSDS) is available for each product. Users should consult the MSDS, and follow the precautions outlined and comply with all laws and regulations concerning its use and disposal. Used packaging material should not be incinerated or exposed to flame. After use, protect your environment. Do not pollute drains, soil or water with used product.

The Materials Safety Data Sheet is available at Royal Precision Lubricants by email:  
[info@royallubricants.com.au](mailto:info@royallubricants.com.au).